



RESISTANCE @ +25°C = 2.5 Ω ± 20%  
 MAXIMUM STEADY STATE CURRENT = 9 AMPS  
 RESISTANCE @ MAXIMUM CURRENT = 0.04 Ω NOMINAL  
 DIM "D" = 0.900" MAXIMUM  
 DIM "T" = 0.250" MAXIMUM  
 DIM "L" = 0.900" MINIMUM  
 DIM "S" = 0.310" NOMINAL  
 LEAD GAUGE = 18 AWG OR 20 AWG

SEE MANUFACTURING SPECIFICATION (LAYER 1)

"B"	DIM "L" WAS 1.0" MINIMUM	07/15/09	DD
"A"	DIM "D" WAS 0.900" MAXIMUM & LEAD WIRE GAUGE WAS 20 AWG	07/14/09	DD
---	ISO RELEASE	07/31/03	DD
REV	REVISION RECORD	DATE	APP

SCALE	NONE	<b>U.S. SENSOR CORP.</b> 1832 W. COLLINS AVE. ORANGE, CA . 92867 714-639-1000 www.ussensor.com
DRAWN BY	T. SOMERVILLE	
DATE	09/01/93	
REV.	"B"	
LAYER	0 OF 2	
		INRUSH CURRENT LIMITER
		P/N ST2R509B