

Specification Sheet

Part Number: T120S0UVK2



Heavy Duty Cable Tie, 8.9" Long, UL Rated, 120lb Tensile Strength, PA66UV, Black, 50/pkg

Article Number	111-12860
Type	T120S
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• UV stabilized heavy-duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description

Heavy Duty Cable Tie, 8.9" Long, UL Rated, 120lb Tensile Strength, PA66UV, Black, 50/pkg

Global Part Name

T120S-PA66UV-BK

Minimum Tensile Strength (Imperial)

120.0

Minimum Tensile Strength (Metric)

535.0

Length L (Imperial)

8.9

Length L (Metric)

225.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.30

Width W (Metric)

7.6

Bundle Diameter Min (Imperial)

0.20

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

2.2

Bundle Diameter Max (Metric)

55.9

Thickness T (Imperial)

0.06

Thickness T (Metric)

1.6

Material

Polyamide 6.6 UV-resistant (PA66UV)

Material Shortcut

PA66UV

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

UL-ZODZ2.E64139

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

50

Package Quantity (Metric)

50

Customs Number

3926909987

Weight (Metric)

4.7

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)