

Specification Sheet

Part Number: 156-00074



Heavy-Duty Fir Tree Mount Cable Tie, 15" x .5", .04"-.62" Panel Thick, PA66HIRHSUV, Black, 100/pkg

| | |
|---------------------|--|
| Article Number | 156-00074 |
| Type | WSRFT9B |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• The "H" profile provides a broad surface contact to minimize the pinching of bundles.• Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.• Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications. |
| Quantity Per | bag |
| Product Description | HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie. |

| | |
|--|--|
| Short Description | Heavy-Duty Fir Tree Mount Cable Tie, 15" x .5", .04"-.62" Panel Thick, PA66HIRHSUV, Black, 100/pkg |
| Global Part Name | WSRFT9B-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 120.0 |
| Minimum Tensile Strength (Metric) | 535 |
| Length L (Imperial) | 15.0 |
| Length L (Metric) | 380.0 |
| Fixation Method | Fir Tree |
| Identification Plate Position | none |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.5 |
| Width W (Metric) | 12.7 |
| Bundle Diameter Max (Imperial) | 4.1 |
| Bundle Diameter Max (Metric) | 105.0 |
| Height H (Imperial) | 1.12 |
| Height H (Metric) | 28.40 |

| | |
|--|--|
| Panel Thickness Min(Imperial) | 0.039 |
| Panel Thickness Max(Imperial) | 0.622 |
| Panel Thickness Min (Metric) | 1.0 |
| Panel Thickness Max (Metric) | 15.8 |
| Mounting Hole Diameter D (Imperial) | 0.34 - 0.36 |
| Mounting Hole Diameter D (Metric) | 8.7 - 9.2 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.34 |
| Mounting Hole Diameter D Max (Imperial) | 0.36 |
| Mounting Hole Diameter D Max (Metric) | 9.25 |
| Disc Diameter(Metric) | 21.6 |
| Disc Diameter (Imperial) | 0.85 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Operating Temperature (Metric) | -67°F to +212°F (-55°C to +100°C) |
| Reach Complaint(Article 33) | Yes |

ROHS Complaint

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987

Content Unit(BMEcat)

pcs.