

Specification Sheet

Part Number: S2CM258HIRHSH1



Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHS, Gray, 500/pkg

Article Number	151-29400
Type	S2CM25
Color	Gray (GY)
Features & Benefits	<ul style="list-style-type: none">•Separates bundles from wear and chafing, providing additional longevity.•Hexagonal retention feature (S2HM25) captures a bolt or nut requiring tool access from the back side only. •A socket counterbore allows securing with a socket wrench from the top side for use with a weld stud or bolt (S2CM25.)•Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.
Quantity Per	bag

Product Description

HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, the H-profile on the saddle mount provides a tight circumferential loop on large and small bundles. Cable ties up to 1/2" wide are used to secure the bundles.

Short Description

Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHS, Gray, 500/pkg

Global Part Name

S2CM25-PA66HIRHS-GY

Length L (Imperial)

1.80

Length L (Metric)

45.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

1.2

Width W (Metric)

30.0

Bundle Diameter Max (Imperial)

3.5

Bundle Diameter Max (Metric)

89.0

Cable Ties

T50 - T250

Height H (Imperial)

0.90

Height H (Metric)

23.0

Cable Tie Width Max (Imperial)

0.5

Cable Tie Width Max (Metric)

12.7

Mounting Hole Diameter D (Imperial)

0.24

Mounting Hole Diameter D (Metric)

6.0 mm

Mounting Hole Diameter D Min (Imperial)	0.24
--	------

Mounting Hole Diameter D Max (Imperial)	0.24
--	------

Mounting Hole Diameter D Max (Metric)	6.0
--	-----

Stud Diameter (Metric)	6.35 mm
-------------------------------	---------

Stud Diameter (Imperial)	0.25
---------------------------------	------

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
-----------------	--

Material Shortcut	PA66HIRHS
--------------------------	-----------

Flammability	UL 94 HB
---------------------	----------

Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
---------------------------------------	-----------------------------------

Reach Complaint(Article 33)	Yes
------------------------------------	-----

ROHS Complaint	Yes
-----------------------	-----

Package Quantity(Imperial)	500
-----------------------------------	-----

Package Quantity (Metric)	500
----------------------------------	-----

Customs Number	3926909987
-----------------------	------------

Content Unit(BMEcat)	pcs.
-----------------------------	------

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)