



FEATURES



- Blue thermoplastic elastomer, copolyester construction
- Patented* latching mechanism adjusts the wristband's diameter from 1.7 to 2.6 inches
- Interior wristband resistance: $< 1 \times 10^5$ ohms
- Exterior wristband resistance: $> 1 \times 10^7$ ohms
- Unique dual contact design is to be paired with an [SCS MagSnap 360™ Dual-Wire Coil Cord](#) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- Backplate Material: Stainless-steel
- Compatible with [SCS Dual-Wire Workstation Monitors](#) and other brands that accept a 3.5 mm phono plug.
- Meets requirements of ANSI/ESD S20.20, ANSI/ESD S1.1, EN 61340-5-1 and IEC 61340-4-6
- May be cleaned with water and mild detergent or 10% isopropyl solution

Item	Description
2240	Wristband Only
2241	Wristband with 6' Coil Cord
2242	Wristband with 12' Coil Cord

Unless otherwise noted, tolerance $\pm 10\%$

Specifications and procedures subject to change without notice.

*U.S. Patent 6,256,847



Made in the
United States of America

SCS

MAGSNAP 360™ DUAL-WIRE THERMOPLASTIC WRISTBAND

SCS

920 J R INDUSTRIAL DRIVE, SANFORD, NC 27332
EAST: (919) 718-0000 | WEST: (909) 627-9634
WEBSITE: StaticControl.com

**DRAWING
NUMBER**

2240

DATE

January
2018