



used for: D-SUB COMBINATION

1
3
2

NOTES:

- 1. MATERIAL: COPPER ALLOY
- 2. PLATING:
 ITEM 1: min. 30µ" HARD GOLD OVER min. 50µ" NICKEL
 ITEM 2: min. 8µ" HARD GOLD OVER min. 50µ" NICKEL
 ITEM 3: NICKEL PLATED

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

		tolerance ISO 2768-m			
		2002	date	name	
		drawn	26.07.	Parei	
		appd.	26.07.	E. Mickenbecker	
		norm			
		d-old			
2 x c	Ä 1615	21.08.2002	Parei		
1 x b	Ä 1603	08.08.2002	Parei		
rev.	description	date	name		

scale: 5:1	
material: SEE NOTES	
title: HIGH POWER CONTACT MALE (b) CRIMP / SOLDER VERSION 90° - 30A D-SUB COMBINATION	
dwg no:	AutoCAD
13K1A657	
part no:	131C16039X
DIN-A 4 sh: 1/1	

A

A